

ADVANCED Surveillance Solution

Qian POE IP Camera 5MP Bullet



Higher Resolution Support

The 1/3" progressive scan CMOS sensor ensures accurate monitoring and enhanced security.

Micro SD Card Slot support 256GB

Allows the camera to store footage directly on the card, eliminating the need for external storage devices or network storage systems. This provides a convenient and cost-effective solution for recording and storing video data.



High-Quality Imaging

With maximum resolution of 2560×1920@20fps, it provides exceptional image quality with its maximum resolution, allowing you to capture detailed visuals and see fine details clearly.





Qian POE IP Camera 5MP Bullet QEC-IBUL5



DATASHEET (QEC-IBUL5)

Image Sensor	1/3" Progressive Scan CMOS
Maximum Resolution	2560(H)×1920(V)
Electronic shutter	Auto/Manual, 1/5 ~ 1/20,000s
Minimum Illumination	Color: 0.1 Lux @ (F1.6,AGC ON) ,B/W: 0 Lux @ (IR LED ON)
Signal to Noise Ratio S/N	55 dB
Day-Night Mode	Auto/ Day/ Night/ Timing
Wide Dynamic Range	DWDR
IR Range	Up to 30 m (98.4 ft)
IR On/Off Control	Auto/Manual
Pan/Tilt/Rotation Range	Pan: 0° ~ 360°, Tilt: 0° ~ 90°, Rotation: 0° ~ 360°
Lens Type	Fixed focal
Iris	Fixed Iris
Focal length	2.8 mm
F Number	F 2.0
Angle of View	H: 93.2°, V: 50.2°
video compression code rate	H.264/ H.265/ H.265+(Smart Encode)
Streaming Capability	2 streams
Stream/Frame Rate	Main Stream: 2560×1920, 2560×1440, 2304×1296, 1920×1080, 1280×720, 704×576 @ 20fps Sub Stream: 640×360 @ 20fps
Bit Rate	CBR/VBR, Main Stream: 512kbps ~ 6144kbps, Sub Stream: 128kbps ~ 1536kbps
Image Adjustment	Brightness/Sharpness/Contrast/Saturation
White Balance	Auto/Manual
Support Features	Mirror, Motion Detection, Privacy Masking, Human Detection, Reset Button
Digital noise reduction	2D/3D NR
Image Enhancement	DWDR/HLC/BLC/Defog
Protocols	IPv4, RTSP/RTP/RTCP, TCP/UDP,DHCP, DNS, DDNS, UPNP, ICMP, IGMP, NTP, SMTP, 802.1x, SNMP, HTTP/HTTPS, PPPOE
Interoperability	ONVIF, SDK
Max. User Access	4 Users
Web Viewer	<IE11, Chrome, Firefox, Microsoft Edge
Management Software	InView Pro/ CMS
Smart Function	Intrusion and Line crossing detection based on human detection
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
Operating and Storage Temperature	Storage
Storage	DC12V/POE (IEEE 802.3af)
Power Consumption	Max 5W
Operating temperature	-25°C ~ 55°C (-13°F ~ 131°F)
Operating humidity	Less than 90% RH
Ingress Protection	IP66
Certifications	CE/ FCC
Casing	Metal
Dimensions	181.9 × 66.26 × 66.17 mm (7.16 × 2.61 × 2.60 inch)
Net weight	0.35 kg (0.77 lb)

EAN

7500619011402